

MODEL 600 FX SERIES COFFEE GRANULIZER

PRECISION GRINDING Technology for Industrial Coffee Applications



Model 600 FX.WC (Water-Cooled) Coffee Granulizer
Two (2) Grinding Section Configuration with Integrated Normalizer

SPECIFICATIONS

- Roll Size:** 6 x 8 inches [152 x 203 mm]
- Sections:** Two (2) or three (3) stacked grinding sections
- Power:** 10 HP [7.5 kw] 50 or 60 hz
- Drawing(s):** Available for download on website

The Model 600 FX is the world's smallest, true industrial roller-style coffee grinder. Exceptional particle size performance on a range of grind sizes and consistent results differentiate the 600 FX from other grinder designs. Additionally, the 600 FX offers a number of options, such as PLC control, water-cooling and density control to further improve ground coffee quality and consistency.

ACCOMODATES ALL GRIND SIZES

COARSE/SOLUBLE	PODS
REGULAR	ESPRESSO
DRIP	FILTER FINE



MODERN PROCESS EQUIPMENT CORPORATION

THE WORLD'S LEADING MANUFACTURER OF COFFEE GRINDING EQUIPMENT

Model	Grinding Sections	Normalizer	Approximate Capacity (lbs/hr)							Traditional Grind Range [average size in microns]	
			0	250	500	750	1,000	1,250	1,500		
600 FX	2-3	Y			Espresso	Filter				Espresso	200 - 450 microns
600 FS	1-2	N							Soluble/Instant	Filter	500 - 1,000 microns
										Soluble	1,000 - 2,500 microns

FEATURES:




Infinite Roll Gap Adjustment

Grind adjustment is achieved using a manual adjustment mechanism (Settings 1 - 10), which can be quickly and easily adjusted to achieve roll gap accuracies of +/-0.001" (0.02mm). A semi-automatic control panel features push button style controls with optional digital gap indication.

Rugged Construction and Spring-mounted Rolls

Heavy-duty construction and oversized double spherical roller bearings provide a long service life, reduced vibrations and maintain tight tolerances under extreme conditions. Spring mounted rolls prevent damage to rolls from foreign materials.




Roll Surface Options and Precision Tolerances

MPE manufactures its own tools used to corrugate rolls and offers thousands of tooth sizes and profiles for each unique application and grind size - course (urn) to fine (espresso).

Integrated Normalizer with Density Control and Chaff Reduction

The Model 600 features an integrated Normalizer designed to both eliminate the visual presence of chaff and continuously control the coffee density to meet coffee product and packaging requirements. Both **manual** and **automated** Normalizer systems are offered.



Water-Cooled Rolls and Coffee Temperature Systems

Heat elimination in the grinding and normalizing (homogenizing) process **preserves the coffee volatile oils and aroma** and prevents a "second roast" during grinding. The 800 Series normalizer features veined water channels and the largest surface area in the industry.



High Torque Drive (HTD)

The HTD drive system provides quiet, lubrication free operation with a wide range of speed and differential capabilities.

Additional Options

- Stainless steel or electroless-nickel construction
- High hardness roll coatings for extreme wear resistance
- Closed-loop water-chiller with variable temperature control
- Semi-automatic or PLC control systems
- Integrated magnet
- Gas-tight Construction

MODERN PROCESS EQUIPMENT CORPORATION

mpechicago.com
solution@mpechicago.com

3125 South Kolin Avenue
Chicago, Illinois 60623
U.S.A.

P +1 773 254 3929
F +1 773 254 3935

