

MODEL **700 FX** SERIES COFFEE GRANULIZER

PRECISION GRINDING TECHNOLOGY FOR INDUSTRIAL COFFEE APPLICATIONS



The Model 700 FX is one of the world's most popular industrial coffee grinders. Exceptional particle size performance on a range of grind sizes and consistent results differentiate the 700 FX from other grinder designs. Additionally, the 700 FX offers a number of options, such as PLC control, water-cooling and density control to further improve ground coffee quality and consistency.

Model 700 FX.WC (Water-Cooled) Coffee Granulizer
Two (2) Grinding Section Configuration with Integrated Normalizer

SPECIFICATIONS

- Roll Size:** 6 x 18 inches [152 x 457 mm]
- Sections:** Two (2) or three (3) stacked grinding sections
- Power:** 10 HP [7.5 kw] 50 or 60 hz
- Drawing(s):** Available for download on website

ACCOMMODATES ALL GRIND SIZES

COARSE/SOLUBLE	PODS
REGULAR	ESPRESSO
D RIP	FILTER FINE



MODERN PROCESS EQUIPMENT CORPORATION • MPECOFFEE.COM

3125 SOUTH KOLIN AVENUE CHICAGO, ILLINOIS 60623, USA • SOLUTION@MPECHICAGO.COM • P: +1 773.254.3929 • F: +1 773.254.3935

Model	Grinding Sections	Normalizer	Approximate Capacity (lbs/hr)						
			0	500	1,000	1,500	2,000	2,500	3,000
700 FX	2-3	Y			Espresso	Filter			
700 FS	1-2	N						Soluble/Instant	

Traditional Grind Range
[average size in microns]

Espresso	200 - 450 microns
Filter	500 - 1,000 microns
Soluble	1,000 - 2,500 microns

FEATURES




INFINITE ROLL GAP ADJUSTMENT

Grind adjustment is achieved using a manual adjustment mechanism (Settings 1 - 10), which can be quickly and easily adjusted to achieve roll gap accuracies of $\pm 0.001"$ (0.02mm). A semi-automatic control panel features push button style controls with optional digital gap indication.

RUGGED DESIGN & CONSTRUCTION

Heavy-duty construction and oversized double spherical roller bearings provide a long service life, reduced vibrations and maintain tight tolerances under extreme conditions.




ROLL SURFACE OPTIONS & PRECISION TOLERANCES

MPE manufactures its own tools used to corrugate rolls and offers thousands of tooth sizes and profiles for each unique application and grind size - course (urn) to fine (espresso).

INTEGRATED NORMALIZER WITH DENSITY CONTROL & CHAFF REDUCTION

The Model 700 features an integrated Normalizer designed to both eliminate the visual presence of chaff and continuously control the coffee density to meet coffee product and packaging requirements. Both **manual** and **automated** Normalizer systems are offered.



WATER-COOLED ROLLS & COFFEE TEMPERATURE SYSTEMS

Heat elimination in the grinding and normalizing (homogenizing) process **preserves the coffee volatile oils and aroma** and prevents a "second roast" during grinding. The 700 Series normalizer features veined water channels and the largest surface area in the industry.

HIGH TORQUE DRIVE (HTD)

The HTD drive system provides quiet, lubrication free operation with a wide range of speed and differential capabilities.

ADDITIONAL OPTIONS

- Stainless steel or electroless-nickel construction
- High hardness roll coatings for extreme wear resistance
- Closed-loop water-chiller with variable temperature control
- Semi-automatic or PLC control systems
- Integrated magnet
- Gas-tight Construction

